

GEHL Authorized Dealer

Sales • Service • Parts

Of Houston



20934 I-45 N-Freeway



Spring, Texas, 77373

281-651-6666

- Home
- Skid Loaders
- Track Loaders
- Excavators
- Demos
- Pre-Owned
- Service
- Location
- Contact

Compact Track Loaders

SPECIFICATIONS



CTL75 COMPACT TRACK LOADER

Forecast says rain; Track Loaders say, "Bring it On." With the unique ability to work in soft, boggy and muddy conditions, operators no longer have to experience down time in wet conditions. With the wide contact area of the tracks on the ground, push power is extremely strong for tackling a dirt pile or using a dozer blade.

- Rated Op. Capacity - 50% Tipping Cap. (kg): 2976 lbs. (1350)
- Rated Op.Capacity - 35% Tipping Cap. (kg): 2083 lbs. (945)
- Horsepower (kW): 83 hp (62) @ 2500 rpm
- Maximum Lift Height (mm): 122.9" (3120)
- Width - w/bucket (mm): 74" (1880)
- Length w/ bucket (mm): 147.2" (3740)

STANDARD EQUIPMENT

- All-Tach™ Attachment Mounting System
- Back-up Alarm
- Dual-Element Air Cleaner with Indicator
- Dual, interior cab-mounted rear view mirrors
- Electric Switch Auxiliary Hydraulic Control
- Electrohydraulic Push Button - Lift Arm Float Feature
- Elevated Planetary Final Drives with SAHR Disc Brakes
- Engine Automatic Shutdown System
- Fuel, Engine, Temperature and Hourmeter Gauges
- Full Suspension Seat - 6-way Adjustable
- Glow Plug Starting
- Hand Throttle
- Horn
- Hydraulic Self-Leveling
- Independent Hydraulic Reservoir with Cooler
- Interlock System for Lift, Tilt Cylinders, Auxiliary Hydraulic Functions and Drives
- Joystick (Hydraulic Pilot-operated) "Hands-Only" controls
- Mechanical Lift Cylinder Lock
- Operator Restraint Bar with Armrests and Adjustable Seatbelt
- Operational Lights - Two front, two rear halogen lights
- ROPS/FOPS - Level I Approved Overhead Guard
- Rubber Track Undercarriage System
- Servo-Controlled Hydrostatic Drive
- Swing-Out Radiator and Hydraulic Oil Cooler
- Two-Speed Hydrostatic Drive System
- Vandalism Lock Provisions - Engine Cover/Rear Door/Fuel Cap
- Warning Lights
- Yanmar Liquid-Cooled Diesel Engine

OPTIONAL EQUIPMENT

- Generation II Heating and Air-Conditioning with Sealed and Pressurized Cab
- Dual Hand Controls
- Foot Throttle Kit

| | |
|------------------------------|---------------------------|
| SPECIFICATIONS | CTL75 |
| ENGINE | |
| Make | Yanmar |
| Model | 4TNV98T |
| Aspiration | Turbo-Charged |
| Displacement (L) / cylinder | 202.5 cu.in. (3.3) / 4 |
| Horsepower (kW) @ rpm | 83 hp (62) @ 2500 |
| Maximum Torque (Nm) @ rpm | 219 ft.-lbs. (297) @ 1800 |
| PERFORMANCE | |
| Tipping Load - SAE J732 (kg) | 5952 lbs. (2700) |
| Rated Operating Load | |

| | |
|---|------------------------|
| SAE J818 @ 50% Tipping Capacity (kg) | 2976 lbs. (1350) |
| SAE J818 @ 35% Tipping Capacity (kg) | 2083 lbs. (945) |
| Breakout Force (kN) | |
| - Bucket | 7401 lbs. (32.9) |
| - Lift Arm | 7425 lbs. (33) |
| | |
| ELECTRICAL | |
| Battery/CCA | 12-volt / 660 |
| Alternator | 50 amp |
| | |
| UNDERCARRIAGE | |
| Traction Pump/Traction Drive | Piston / Planetary |
| Traction Braking | Hydraulic |
| Drawbar Pull (kN) | 11,067 lbf (50) |
| Roller Type / Track Rollers - Each Side | Steel / 4 |
| Track Width | 18" (457) |
| Track Contact Length | 59" (1496) |
| Ground Pressure (kg/cm ²) | 4.3 psi (0.29) |
| Travel Speed | |
| - Low | 0-4.7 mph (0-7.6) |
| - High | 0-7.2 mph (0-11.6) |
| | |
| HYDRAULIC SYSTEM | |
| Operating Pressure (bar) | 2988 psi (206) |
| Auxiliary Hydraulic Flow - standard (L/min) | 19.8 gpm (74.9) |
| Auxiliary Hydraulic Flow - option (L/min) | 36.3 gpm (137.5) |
| | |
| CAPACITIES | |
| Fuel Tank (L) | 23.8 gal. (90.1) |
| Hydraulic Reservoir (L) | 12.8 gal. (48.5) |
| Engine Oil (L) | 10.8 qts. (10.2) |
| Engine Coolant (L) | 17.4 qts. (16.5) |
| | |
| DIMENSIONS AND WEIGHTS | |
| Operating Weight - Approximate (kg) | 9700 lbs. (4400) |
| Maximum Lift Height to Bucket Pin (mm) | 122.9" (3120) |
| Dump Height (mm) | 94.8" (2405) |
| Reach at Maximum Lift (mm) | 34.4" (874) |
| Dump Angle | 38.5° |
| Bucket Rollback at Ground Level (mm) | 31° |
| Length - Without Bucket (mm) | 117.3" (2980) |
| Length - With Bucket (mm) | 147.2" (3740) |
| Ground Clearance (mm) | 12.8" (325) |
| Angle of Departure | 30° |
| Height - to top of ROPS (mm) | 85" (2167) |
| Width - Without Bucket (mm) | 70" (1770) |
| Width - With Bucket (mm) | 74" (1880) |
| Rear Clearance Radius (mm) | 66" (1666) |
| Front Clearance Radius - With Bucket (mm) | 90" (2294) |
| | |
| BUCKET | |
| Mounting | Universal Quick-Attach |
| Capacity - SAE Heaped (m ³) | 17.0 cu. ft. (0.48) |

[back to track loaders](#)

[top of page](#)